# Copper Lay-In Ground Lug
## Direct Burial

RoHS Compliant


UL LISTED 667P

SA LR-29601

TYPE
# CGBL

**Features**
- Lay-in feature
- Manufactured from high strength copper
- Stainless steel hardware

**Benefits**
- Provides ease of installation of continuous loop grounding conductor
- Suitable for direct burial and for use with copper conductors
- Resists oxidation and corrosion in earth or concrete







Fig. 1



Fig. 2

| Catalog Number | Figure Number | Ground Wire Range | Bolt Size | Dimensions | | | | | | | Screw Type |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | C | D | E | F | G | H | T | |
| GBL-4DB | 1 | 4-14 | 10 | .218 | .680 | .470 | 1.150 | .190 | .375 | .825 | Slot |
| GBL-4DB-14 | 1 | 4-14 | 1/4 | .265 | .680 | .470 | 1.150 | .210 | .472 | .825 | Slot |
| *+ GBL-4DBT | 1 | 4-14 | 10 | .218 | .680 | .470 | 1.150 | .190 | .375 | .825 | Slot |
| * GBL-4DBT-14 | 1 | 4-14 | 1/4 | .265 | .680 | .470 | 1.150 | .210 | .472 | .825 | Slot |
| *+ GBL-4DBTH | 2 | 4-14 | 10 | .218 | .680 | .470 | 1.150 | .190 | .375 | .825 | Hex |
| * GBL-4DBTH-14 | 2 | 4-14 | 1/4 | .265 | .680 | .470 | 1.150 | .210 | .472 | .825 | Hex |

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 467, UL File E34440
* T indicates tin plating
+ GBL-4DBT and GBL-4DBTH are UL2703 Listed UL E354420 Vol. 2
Optional MH Series mounting hardware kits available, consult ILSCO