



SIL-320 NL



60 Cell Monocrystalline PV Module



CHUBB®

* Chubb provides error and omission insurance to Silfab Solar Inc.

INDUSTRY LEADING WARRANTY


All our products include an industry leading 25-year product workmanship and 30-year performance warranty.

35+ YEARS OF SOLAR INNOVATION

Leveraging over 35+ years of worldwide experience in the solar industry, Silfab is dedicated to superior manufacturing processes and innovations such as Bifacial and Back Contact technologies, to ensure our partners have the latest in solar innovation.

NORTH AMERICAN QUALITY

Silfab is the leading automated solar module manufacturer in North America. Utilizing premium quality materials and strict quality control management to deliver the highest efficiency, premium quality PV modules 100% made in North America.



■ BAA / ARRA COMPLIANT

Silfab panels are designed and manufactured to meet Buy American Act Compliance. The US State Department, US Military and FAA have all utilized Silfab panels in their solar installations.

■ LIGHT AND DURABLE

Engineered to accommodate low load bearing structures up to 5400Pa. The light-weight frame is exclusively designed for wide-ranging racking compatibility and durability.

■ LOWEST DEFECT RATE

Total automation ensures strict quality controls during the entire manufacturing process at our ISO certified facilities. 48.18 ppm as per December 2018.

■ DOMESTIC PRODUCTION

Silfab Solar manufactures our PV modules in two automated locations within North America. Our 300+ North American team is ready to help our partners win the hearts and minds of customers, providing customer service and product delivery that is direct, efficient and local.

■ AESTHETICALLY PLEASING

All black sleek design, ideal for high-profile residential or commercial applications.

■ PID RESISTANT

PID Resistant due to advanced cell technology and material selection. In accordance to IEC 62804-1.



Electrical Specifications		SIL-320 NL mono PERC			
Test Conditions		STC		NOCT	
Module Power (Pmax)	Wp	320		242	
Maximum power voltage (Vpmax)	V	32.88		29.59	
Maximum power current (Ipmax)	A	9.74		8.18	
Open circuit voltage (Voc)	V	40.10		37.09	
Short circuit current (Isc)	A	10.32		8.46	
Module efficiency	%	18.8		17.8	
Maximum system voltage (VDC)	V			1000	
Series fuse rating	A			20	
Power Tolerance	Wp			0 to +10	
Measurement conditions: STC 1000 W/m² • AM 1.5 • Temperature 25 °C • NOCT 800 W/m² • AM 1.5 • Measurement uncertainty ≤ 3% • Sun simulator calibration reference modules from Fraunhofer Institute. Electrical characteristics may vary by ±5% and power by 0 to +10W.					
Temperature Ratings		SIL-320 NL mono PERC			
Temperature Coefficient Isc		0.064 %/°C			
Temperature Coefficient Voc		-0.28 %/°C			
Temperature Coefficient Pmax		-0.36 %/°C			
NOCT (± 2°C)		45 °C			
Operating temperature		-40/+85 °C			
Mechanical Properties and Components		SIL-320 NL mono PERC			
		Metric		Imperial	
Module weight		18.6 kg ±0.2 kg		41 ±0.4 lbs	
Dimensions (H x L x D)		1700 mm x 1000 mm x 38 mm		66.9 in x 39.4 in x 1.5 in	
Maximum surface load (wind/snow)*		4000 Pa rear load / 5400 Pa front load N/m²		83.5/112.8 lb/ft^2	
Hail impact resistance		ø 25 mm at 83 km/h		ø 1 in @ 51.6 mph	
Cells		60 - Si mono PERC - 5 busbar 158.75 x 158.75 mm		60 - Si mono PERC - 5 busbar 6.25 x 6.25 Inch	
Glass		3.2 mm high transmittance, tempered, DSM anti-reflective coating		0.126 high transmittance, tempered, DSM anti-reflective coating	
Cables and connectors (refer to installation manual)		1200 mm, ø 5.7 mm, MC4 compatible		47.2 in, ø 0.22 in, MC4 compatible	
Backsheet		High durability, superior hydrolysis resistance, multi-layer dielectric film			
Frame		Anodized Aluminum (Black)			
Bypass diodes		3 diodes-30SQ045T (45V max DC blocking voltage, 30A max forward rectified current)			
Junction Box		UL 3730 Certified, IP67 rated			
Warranties		SIL-320 NL mono PERC			
Module product workmanship warranty		25 years**			
Linear power performance guarantee		30 years			
		≥ 97% end 1 st year	≥ 90% end 12 th year	≥ 82% end 25 th year	≥ 80% end 30 th year
Certifications		SIL-320 NL mono PERC			
Product		ULC ORD C1703, UL 1703, CEC listed, IEC 62716 Ammonia Corrosion; IEC61701:2011 Salt Mist Corrosion Certified, UL Fire Rating: Type 2			
Factory		ISO9001:2015			

- Modules Per Pallet: 26
- Pallets Per Truck: 36
- Modules Per Truck: 936

*⚠ Warning. Read the Safety and Installation Manual for mounting specifications and before handling, installing and operating modules.

**12 year extendable to 25 years subject to registration and conditions outlined under "Warranty" at www.silfabsolar.com.

Third-party generated pan files from Fraunhofer-Institute for Solar Energy Systems ISE are available for download at: www.silfabsolar.com/downloads



Silfab Solar Inc.
240 Courtneypark Drive East
Mississauga ON L5T 2Y3 Canada
Tel +1 905-255-2501 | Fax +1 905-696-0267
info@silfabsolar.com | www.silfabsolar.com



Silfab Solar Inc.
800 Cornwall Ave
Bellingham WA 98225 USA
Tel +1 360-569-4733

