


SLP160-12U

High Efficiency Polycrystalline PV Module

Electrical Characteristics	SLP160-12U
	SLF 100-120
Product code	160011206
Maximum power (Pmax)	160W
Voltage at Pmax (Vmp)	18.65V
Current at Pmax (Imp)	8.58A
Open-circuit voltage (Voc)	22.83V
Short-circuit current (Isc)	9.13A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/ °C
Temperature coefficient of power	_(0.5±0.05)%/ °C
NOCT (Air 20°C; Sun 0.8kW/m ² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%

*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C *NOCT:Nominal operating cell temperature (the data is only for reference)

Module Diagram



Dimensions in brackets are in inches. Un-bracketed dimensions are in millimeters. Unit: mm[in.]



Junction Box Top View(Lid Open)




Section A-A

Features

- Nominal 12V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

Characteristics



Specifications	SLP160-12U
Cells	Polycrystalline silicon solar cell
No. of cells and connections	36(4X9)
Module dimension	1500mm[59.06in.]x675mm[26.57in.]x35mm[1.38in.]
Weight	12.0kg[26.46lbs]
Packing information(Carton)	1545mm[60.83in.]x720mm[28.35in.]x70mm[2.76in.]/(1pc/ctn)

*Limited warranty: 5-year limited warranty of materials and workmanship; 10-year limited warranty of 90% power output; 25-year limited warranty of 80% power output. For detail, please contact us. *Specifications are subject to change without notice at any time.